



Congratulations!

You have purchased a quality U.S.A. made container for your vehicle's wheel chock.

Depending on your company's unique requirements, the dock-n-chock container is designed to be mounted in most convenient locations. The most common place would be on the left / drivers side of vehicle or trailer, located just forward of the rear wheels.

*Mount flush with the outside edge of truck/trailer, this will allow the door and flag to extend and be seen.

***Four 7/16 holes** for DNC-1F (the single chock holder)

***Six 7/16 holes** for DNC -2F (the double chock holder) Swing flag slider up and push 1st chock to the back of box, drop flag slider and push slider with the second chock, close door and secure with the latch handle.

*Drill these holes on underside flanges of the "I" beam of the box truck/trailer. The hole pattern can be traced using the shipping box as a template and from the dock-n-chock unit.

*Tighten the bolts only after fully assembled and in place on the vehicle.



>>>When choosing a wheel chock for this container: It cannot be over 5.5 inches high. To fully benefit from this purchase, select a wheel chock that is of equal quality, one that will not crush the first time used. Wheel chocks with the handle feature makes for ease of use but is not necessary.

Once again, congratulations on your purchase. It is clear to see the value in having a quality storage container ready for use, especially, with the smart notification flag as a one of a kind feature.

*Send questions to docknchock@live.com SEE WWW.dock-n-chock.com OR call 720.879.2861